100 Ω





RamCAT-Flex AWG 26/19 - S/UTP - PUR

- S/UTP (braid + unshielded twisted pairs)
- flexible, stabilizing intermediate jackets from TPE
- 4 x 2 x 0.15 mm² (AWG 26/19) 100 0hm
- low-temperature-flexible down to -40 °C
- robust PUR overall jacket
- EtherSound™ tested by Digigram up to 75 m
- GLD and iLive ACE/dSnake tested by Allen&Heath up to 120 m
- Dante[™] tested by YAMAHA UK up to 75 m

Ultra-rugged, non-crush CAT5-flex data and network cable for mobile applications and drum storage. Suitable for A-Net, AVB (Audio/Video Bridging over Ethernet), CobraNet, Dante™ (AVB), Ether Sound **M* (Trademark of Digigram), RAVENNA (AVB) etc. In contrast to common "CAT5-flex" cables this special cable offers flexibility and sturdiness, which is otherwise only usual with stage cables like microphone lines but not in data systems technology. The transmission interference of standard data cables, along with too small bending radii or mechanical strain is avoided with Klotz RC5 by expensive construction and exceptional material. Different to so called flexible data patch cables, which are designated for indoor use, this RAMCAT cable combines values, that distinguish it for use on stage or at outdoor events.

design

conductor stranded bare copper, 19 x 0.10 mm

core insulation Foam-Skin PE

core stranding 2 cores twisted to a pair cable stranding 4 pairs twisted

inner jacket

overall shield tinned copper braid, >80% coverage

overall diameter 6.3 mm

electric

< 130 Ω/km conductor resistance mutual capacitance 50 pF/m characteristic impedance $100 \Omega \pm 15\%$ properties min. bending radius 5x overall diameter working temperature -40°C / +85°C halogen-free acc. to IEC 60754-1

frequency [MHz]	attenuation [dB/100m]	Next [dB]	
1	1.8	73	
4	4.7	65	
10	8.7	52	
16	11.3	50	
20	12.9	51	
31.25	16.5	45	
62.5	24.4	43	
100	31.8	42	

order code	type	outer jacket	cable color	weight kg/m	standard lengths m
RC5-LB1V	S/UTP	PUR	claret violet	0.05	50 / 100 / 300 / 500
RC5-LB1S	S/UTP	PUR	black	0.05	100 / 300 / 500

technical specifications are subject to change

KLOTZ AIS GmbH

